

Interfibe Fiber Guide

Product	lbs./Bag	Alpine Sieve Retention Fiber Length - % retained				Oil Absorption (*)	Stormer - KU (**)	Brookfield - cPs (**)	Immobilization grams (#)
		500 mesh	325 mesh	270 mesh	100 mesh				
185 -applications: topping compounds, tundish panels, ladle liners, hot top fiber boards, continuous casting applications, extruded sealants, rubberized asphalt/sealants	40	82	73	70	36	7.8	139	N/A	6
230 -applications: disk pads, truck block brake lining friction, asphalt roof cement, asphalt roof coating, gaskets	40	78	69	66	28	7.5	127	N/A	6.4
ETF -applications: asphalt roof coating, roll linings, brake lining friction products, disk pads, gaskets	40	71	63	58	20	7.9	136	N/A	4.9
JMC -applications: asphalt roof coating, brake lining friction products, disk pads, asphalt roof cement	40	68	55	50	10	7.7	110	N/A	6.8
JMM -applications: asphalt roof coating, roll linings, grouts	50	67	52	49	5	6.9	101	3000	7.9
FT -applications: rubber gaskets, v-belts, neoprene, EPDM rubber hose, acrylic tennis court coatings, texture coatings, aluminum roof coating, gunnable (cartridge) butyl sealant, cushion coats for recreational surfaces, rubberized cold-pour crack fillers, asphalt pavement resurfacers, acrylic roof coating	50	64	48	42	2	5.4	88	1658	8.8
GC66 -applications: extruded (tape) products, aluminum roof coating, gunnable (cartridge) butyl sealant	50	56	39	31	0	4.5	68	672	10
GEL-CEL 10 -applications: asphalt undercoating, aluminum roof coating, glue, epoxy mastics, wood putty, block filler, texture coatings, extruded tape	50	52	33	26	0	3.71	68	628	13.5
FTP -applications: acrylic tennis court coatings, cushion coats for recreational surfaces, rubberized cold-pour crack fillers, asphalt pavement resurfacers, tile adhesives, sealcoating	50	65	48	42	2	5.58	88	1658	8.6
5FT -applications: texture coatings, acrylic textured coatings, acrylic roof coating, acrylic block filler, grouts, stucco	50	64	48	42	0	3.88	73	820	11.2
566 -application: acrylic textured paints, acrylic roof coating, stucco, textured coatings, extruded tape, wood putty, epoxy mastic	50	56	39	31	0	3.35	69	659	13.5
GEL-CEL W10 -applications: acrylic textured paints, acrylic roof coating, stucco, textured coatings, extruded tape, wood putty, epoxy mastic	50	48	31	26	0	3.72	65	495	15.8
GEL-CEL W90 -applications: non-textured sealants & epoxies	50	26	9	5	0	2.3	67	448	7.9

(*) Times its own weight

(**) Stormer and Brookfield (3.85% fiber in Kaydol oil)

(#) Grams of fiber in 150 ml of mineral spirits

Distributed by:



CheMarCo, Inc.

P.O. Box 27065
Greenville, SC 29616
Phone: (864) 234-6735
Fax: (864) 234-6975
E-mail: sales@chemarco.com
Internet: www.chemarco.com

Gray

Treated

White